

Cabo Berman

Blindagem Externa



**Proteção anti-roedores e maior isolamento
contra interferências e surtos elétricos.**

Cabo Berman

Blindagem Externa



Cabo com proteção contra roedores e maior isolamento contra interferências e surtos elétricos.

6 fios e 6mm de diâmetro

Dados técnicos

Structure	Project	Main indicators
Conductor	Construction specifications	16/0. 15mm
	Conductor material	Tinned soft copper wire
Insulation	Material	Polyethylene
	Nominal outer diameter	1.3 ± 0.2 mm
	Average insulation thickness	0.3 mm
	Color	White, red, black and blue
Assembly	Nominal pitch	60mm
	Wrapping strap	Aluminum-plastic film
Shield	Knit	Tinned soft copper wire
	Ground wire	Tinned soft copper wire
	Wrapping	Polyester film
Middle quilt	Material	Environmentally friendly PVC
	Color	Grey
	Average sheath thickness	1.2 mm
	Nominal diameter	6mm
Anti-rodent layer	Density	≥90%
	Knit	Tin-plated aluminum-magnesium alloy wire
Outer quilt	Material	Environmentally friendly PVC
	Color	Transparent
	Average sheath thickness	0.7 mm
	Diameter	8 ± 0.2 mm
Performance	Conductor resistance (20 °C)	≤ 71. 2 Q/1000m
	Test voltage	1.0 kV/min No breakdown
	Use Temperature	-15~70°C

Código Weightech

Nome do Produto	Código
Cabo Berman Blindagem Externa	501682